



Screwdriving technology

Automation

Air motors

Air tools

DEPRAG

MICROMAT

MICROMAT-Handheld Screwdrivers straight handle design

from 0.02 to 0.7 Nm (3 to 97 in.oz)

- **The lowest torque capacity, available on the market**
- **Extreme high Torque Accuracy and Repeatability**
- **Slightly larger than a ball point pen**
- **Ergonomic design, long life, low noise**

The DEPRAG-MICROMAT screwdriver excels in the screw assembly to extreme small torque values, down to its minimum capability of 0.02 Nm (3 in.oz). The extremely high torque accuracy of the MICROMAT clutch operates similar to the proven principle of all DEPRAG disconnect- and shut-off clutches.

The pre-set torque value will be held, independent of use of operation, air pressure fluctuations and screw joint.

For ornamental screws with a scratch sensitive surface, we recommend the use of our MICROMAT screwdrivers with an integrated seek-function. This option allows the bit to engage with the screw drive at a lowered speed. Once full down-pressure is applied, the screw is then assembled with the rated full speed.

For this screwdriver type we recommend a possibility of interruption of air supply.



Technical Data

Screwdriver Style		Motor Size 0				Motor Size 0 with seek-function
Screwdriver right-rotation, right shut-off Push-To-Start	type order no.	345-308 339267 A	345-408 345763 A	345-708 385162 A	345-508 339268 A	345-508-2 341337 B
screws	up to	M3	M3	M3	M3	M3
torque	min. Ncm/in.oz	2/3	2/3	2/3	2/3	2/3
soft pull-up	max. Ncm/in.oz	50/70	55/78	70/97	70/97	70/97
hard pull-up	max. Ncm/in.oz	60/83	55/78	70/97	70/97	70/97
speed, idling	rpm	1600	1100	600	350	80/350
air consumption	m ³ /min/cfm	0.1/3.5	0.1/3.5	0.1/3.5	0.1/3.5	0.1/3.5
main body dia.	mm/in.	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆
length	mm/in.	152/6	152/6	158/6 ⁷ / ₃₂	158/6 ⁷ / ₃₂	158/6 ⁷ / ₃₂
weight	kg/lbs	0.15/0.33	0.15/0.33	0.16/0.35	0.16/0.35	0.16/0.35
noise level	dB(A)	65	65	65	65	65
air hose dia.	mm/in.	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈
hose dia. for screw suction	mm/in.	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈
internal hex. drive	DIN 3126	B3 (3 mm/.118")	B3 (3 mm/.118")	B3 (3 mm/.118")	B3 (3 mm/.118")	B3 (3 mm/.118")
Suitable tool inserts and connecting components with a drive as per DIN 3126		A3 (3 mm/.118")	A3 (3 mm/.118")	A3 (3 mm/.118")	A3 (3 mm/.118")	A3 (3 mm/.118")
quick change chuck, mounted		yes	yes	yes	yes	yes
Screwdriver reversible, right shut-off Push-To-Start	type order no.	345-308U 339269 A	345-408U 345764 A	345-708U 385163 B	345-508U 339270 A	345-508 U2 341124 B
screws	up to	M3	M3	M3	M3	M3
torque	min. Ncm/in.oz	2/3	2/3	2/3	2/3	2/3
soft pull-up	max. Ncm/in.oz	40/57	50/70	70/97	70/97	70/97
hard pull-up	max. Ncm/in.oz	50/70	50/70	70/97	70/97	70/97
speed, idling	rpm	1300	950	480	300	70/300
air consumption	m ³ /min/cfm	0.1/3.5	0.1/3.5	0.1/3.5	0.1/3.5	0.1/3.5
main body dia.	mm/in.	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆	17 ¹¹ / ₁₆
length	mm/in.	167/6 ⁹ / ₁₆	167/6 ⁹ / ₁₆	173/6 ¹³ / ₁₆	173/6 ¹³ / ₁₆	173/6 ¹³ / ₁₆
weight	kg/lbs	0.17/0.38	0.17/0.38	0.18/0.40	0.18/0.40	0.18/0.40
noise level	dB(A)	65	65	65	65	65
air hose dia.	mm/in.	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈
hose dia. for screw suction	mm/in.	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈	3 ¹ / ₈
drive hex. female		3 mm/.118"	3 mm/.118"	3 mm/.118"	3 mm/.118"	3 mm/.118"
internal hex. drive	DIN 3126	B3 (3 mm/.118")	B3 (3 mm/.118")	B3 (3 mm/.118")	B3 (3 mm/.118")	B3 (3 mm/.118")
Suitable tool inserts and connecting components with a drive as per DIN 3126		A3 (3 mm/.118")	A3 (3 mm/.118")	A3 (3 mm/.118")	A3 (3 mm/.118")	A3 (3 mm/.118")
quick change chuck, mounted		yes	yes	yes	yes	yes

Performance data relate to an air pressure of 6.3 bar (90 PSI)

Standard Equipment

hose coupling with nozzle, nipple (mounted)
Set of Torque Adjustment Tools
Set of Clutch Springs

Optional Equipment

Exhaust Hose (1 m / 3.28 ft.)	order no.	806113
Spring-Sleeve cpl. (in connection with finder, see leaflet: Inserting Tools D 3320 E)	order no.	364670 A

Please also find tool inserts in our brochure D 3320 E.

DEPRAG

DEPRAG SCHULZ GMBH u. CO.

P.O. Box 1352, D-92203 Amberg, Germany
Kurfürstenring 12-18, D-92224 Amberg
Phone (09621) 371-0, Fax (09621) 371-120
www.deprag.com
info@deprag.de



CERTIFIED AS PER DIN EN ISO 9001