

Handheld Screwdriver pneumatic



MICROMAT/MINIMAT ESD Screwdriver

straight design – torque ranges between 0.02 – 12 Nm



- **robust**
- **uninfluenceably accurate**
- **ergonomic**
- **durable**
- **quiet**

ESD screwdrivers are especially designed for the operation in electrostatic exposed areas, and where an ESD-safe assembly is required (specifications according to EN 100 015). The supplied conductive pressure hose allows a simple, direct and grounded connection, without the need for an additional cable-connection. Between the air-hose for the tool and the main air-outlet an insulating connector can be installed to discharge electrostatic load. The extraordinary constructive quality of the slender MICROMAT/MINIMAT screwdriver and the capability to be used in a heavy industrial environment, assures extreme high up-times.

The ergonomic design of the housing allows a fatigue-proof operation at continued use.

Torque accuracies of < 3% standard deviation and thus Cmk values of ≥ 1.67 with a tolerance of $\pm 15\%$ can be reached * with these screwdrivers. Statistically speaking, the error rate is less than 0.6 per one million screw assemblies.

*) under suitable process conditions

| MICROMAT - straight version | | Motor Size 0 | | | |
|--|---------------------------|--------------------------|--------------------------|---------------------------|---------------------------|
| Screwdriver reversible, right shut-off Push-To-Start | Type Part no. | 345-308UESD 376846A | 345-408UESD 376846B | 345-708UESD 385164A | 345-508UESD 376846C |
| Screws | up to | M 3 | M 3 | M 3 | M 3 |
| Torque min. | Ncm / in.oz | 2 / 2.84 | 2 / 2.84 | 2 / 2.84 | 2 / 2.84 |
| soft pull-up max. | Ncm / in.oz | 40 / 56.8 | 50 / 71 | 70 / 99.4 | 70 / 99.4 |
| hard pull-up max. | Ncm / in.oz | 50 / 71 | 50 / 71 | 70 / 99.4 | 70 / 99.4 |
| Speed, idling | rpm | 1300 | 950 | 480 | 300 |
| Air consumption | m ³ /min / cfm | 0.1 / 3.5 | 0.1 / 3.5 | 0.1 / 3.5 | 0.1 / 3.5 |
| Main body dia. | mm / in. | 17 / 11/16 | 17 / 11/16 | 17 / 11/16 | 17 / 11/16 |
| Length | mm / in. | 167 / 6 ⁹ /16 | 167 / 6 ⁹ /16 | 173 / 6 ¹³ /16 | 173 / 6 ¹³ /16 |
| Weight | kg / lbs | 0.17 / 0.38 | 0.17 / 0.38 | 0.18 / 0.40 | 0.18 / 0.40 |
| Noise level | dB (A) | 65 | 65 | 65 | 65 |
| Air hose dia. | mm / in. | 4 / 5/32 | 4 / 5/32 | 4 / 5/32 | 4 / 5/32 |
| Connector thread for air-hose | | M 5 | M 5 | M 5 | M 5 |
| Hose dia. for screw suction | mm / in. | 3 / 1/8 | 3 / 1/8 | 3 / 1/8 | 3 / 1/8 |
| Internal hex. drive DIN ISO 1173 | | B3 (3 mm/.118") | B3 (3 mm/.118") | B3 (3 mm/.118") | B3 (3 mm/.118") |
| Suitable tool inserts and connecting components with a drive as per DIN ISO 1173 | | A3 (3 mm/.118") | A3 (3 mm/.118") | A3 (3 mm/.118") | A3 (3 mm/.118") |
| Quick change chuck, mounted | | yes | yes | yes | yes |

| MINIMAT - straight version | | Motor Size 1 | | | |
|--|--------------------------|---------------------|---------------------|---------------------|---------------------------|
| Screwdriver reversible, right shut-off Push-To-Start | Type Part no. | 347-218UESD 403345A | 347-318UESD 403345B | 347-518UESD 403345C | 347-618UESD 403345D |
| Screws | up to | M 3 | M 3 | M 3 | M 3 |
| Torque min. | Nm / in.lbs | 0.3 / 2.7 | 0.3 / 2.7 | 0.2 / 1.8 | 0.2 / 1.8 |
| soft pull-up max. | Nm / in.lbs | 1 / 8.85 | 1.4 / 12.4 | 2 / 17.7 | 2 / 17.7 |
| hard pull-up max. | Nm / in.lbs | 1 / 8.85 | 1.4 / 12.4 | 2 / 17.7 | 2 / 17.7 |
| Speed, idling | rpm | 1900 | 1300 | 900 | 600 |
| Air consumption | m ³ /min/ cfm | 0.23 / 8 | 0.23 / 8 | 0.23 / 8 | 0.23 / 8 |
| Main body dia. | mm / in. | 28 / 1 1/8 | 28 / 1 1/8 | 28 / 1 1/8 | 28 / 1 1/8 |
| Length | mm / in. | 190 / 7 1/2 | 190 / 7 1/2 | 190 / 7 1/2 | 198 / 7 ⁵¹ /64 |
| Weight | kg / lbs | 0.4 / 0.9 | 0.4 / 0.9 | 0.4 / 0.9 | 0.43 / 0.95 |
| Noise level | dB (A) | 62 | 62 | 62 | 62 |
| Air hose dia. | mm / in. | 5 / 3/16 | 5 / 3/16 | 5 / 3/16 | 5 / 3/16 |
| Connector thread for air-hose | | 1/8" | 1/8" | 1/8" | 1/8" |
| Hose dia. for screw suction | mm / in. | 3 / 1/8 | 3 / 1/8 | 3 / 1/8 | 3 / 1/8 |
| Internal hex. drive DIN ISO 1173 | | F6.3 (1/4") | F6.3 (1/4") | F6.3 (1/4") | F6.3 (1/4") |
| Suitable tool inserts and connecting components with a drive as per DIN ISO 1173 | | E6.3 (1/4") | E6.3 (1/4") | E6.3 (1/4") | E6.3 (1/4") |
| Quick change chuck, mounted | | yes | yes | yes | yes |

| MINIMAT - straight version | | Motor Size 2 | | | |
|--|--------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Screwdriver reversible, right shut-off Push-To-Start | Type Part no. | 347-228UESD 392476A | 347-328UESD 392476B | 347-428UESD 392476D | 347-528UESD 392476C |
| Screws | up to | M 4 | M 4 | M 4 | M 5 |
| Torque min. | Nm / in.lbs | 0.5 / 4.4 | 0.4 / 3.5 | 0.4 / 3.5 | 0.3 / 2.7 |
| soft pull-up max. | Nm / in.lbs | 1.3 / 11.5 | 2.4 / 21.2 | 3.5 / 31 | 5 / 44.3 |
| hard pull-up max. | Nm / in.lbs | 1.8 / 15.9 | 2.8 / 24.8 | 4 / 35.4 | 5 / 44.3 |
| Speed, idling | rpm | 3000 | 1100 | 750 | 500 |
| Air consumption | m ³ /min/ cfm | 0.3 / 11 | 0.3 / 11 | 0.3 / 11 | 0.3 / 11 |
| Main body dia. | mm / in. | 33 / 1 ⁵ /16 | 33 / 1 ⁵ /16 | 33 / 1 ⁵ /16 | 33 / 1 ⁵ /16 |
| Length | mm / in. | 223 / 8 ²⁵ /32 | 223 / 8 ²⁵ /32 | 223 / 8 ²⁵ /32 | 223 / 8 ²⁵ /32 |
| Weight | kg / lbs | 0.68 / 1.5 | 0.69 / 1.5 | 0.69 / 1.5 | 0.69 / 1.5 |
| Noise level | dB (A) | 67 | 67 | 67 | 67 |
| Air hose dia. | mm / in. | 6.5 / 1/4 | 6.5 / 1/4 | 6.5 / 1/4 | 6.5 / 1/4 |
| Connector thread for air-hose | | 1/8" | 1/8" | 1/8" | 1/8" |
| Internal hex. drive DIN ISO 1173 | | F6.3 (1/4") | F6.3 (1/4") | F6.3 (1/4") | F6.3 (1/4") |
| Suitable tool inserts and connecting components with a drive as per DIN ISO 1173 | | E6.3 (1/4") | E6.3 (1/4") | E6.3 (1/4") | E6.3 (1/4") |
| Quick change chuck, mounted | | yes | yes | yes | yes |

Performance data relate to an air pressure of 6.3 bar (90 PSI)

Included in delivery

Air hose ESD-applicable 1.5 m / 4.9 ft. · Torque adjustment tool · Assortment of clutch springs

| MINIMAT - straight version | | | Motor Size 2.5 | | |
|--|--------------|---------------------------|-------------------------------------|-------------------------------------|-------------------------------------|
| Screwdriver reversible, right shut-off Push-To-Start | | Type Part no. | 345-7258UESD 409631A | 345-3258UESD 409631B | 345-4258UESD 409631C |
| Screws | | up to | M 5 | M 6 | M 6 |
| Torque | min. | Nm / in.lbs | 1 / 8.85 | 1 / 8.85 | 1 / 8.85 |
| | soft pull-up | max. | Nm / in.lbs | 5 / 44.3 | 10 / 88.5 |
| | hard pull-up | max. | Nm / in.lbs | 6 / 53.1 | 10 / 88.5 |
| Speed, idling | | rpm | 1100 | 640 | 310 |
| Air consumption | | m ³ /min / cfm | 0.35 / 12 | 0.35 / 12 | 0.35 / 12 |
| Main body dia. | | mm / in. | 40 / 1 ⁹ / ₁₆ | 40 / 1 ⁹ / ₁₆ | 40 / 1 ⁹ / ₁₆ |
| Length | | mm / in. | 245 / 9 ⁵ / ₈ | 245 / 9 ⁵ / ₈ | 245 / 9 ⁵ / ₈ |
| Weight | | kg / lbs | 0.9 / 2 | 0.9 / 2 | 0.9 / 2 |
| Noise level | | dB (A) | 76 | 76 | 76 |
| Air hose dia. | | mm / in. | 6 / 1/4 | 6 / 1/4 | 6 / 1/4 |
| Connector thread for air-hose | | | 1/8" | 1/8" | 1/8" |
| Internal hex. drive DIN ISO 1173 | | | F6.3 (1/4") | F6.3 (1/4") | F6.3 (1/4") |
| Suitable tool inserts and connecting components with a drive as per DIN ISO 1173 | | | E6.3 (1/4") | E6.3 (1/4") | E6.3 (1/4") |
| Quick change chuck, mounted | | | yes | yes | yes |

Performance data relate to an air pressure of 6.3 bar (90 PSI)

| | |
|-----------------------------|---|
| Included in delivery | Air hose ESD-applicable 1.5 m / 4.9 ft. · Torque adjustment tool · Assortment of clutch springs |
|-----------------------------|---|

| Optional Equipment | | Motor Size 0 | Motor Size 1 | Motor Size 2 | Motor Size 2.5 |
|---|----------|--------------|--------------|--------------|----------------|
| Connection piece (Connector thread 1/4" f / 1/4" m) | Part no. | 378379A | 378379A | 378379A | 378379A |
| Spiral hose, antistatic | Part no. | - | 346697P | 346697P | 346697P |
| Support ring | Part no. | - | 3870323 | 389775B | - |
| Spring sleeve cpl. | Part no. | 364670A | 364672A | 364672A | 364680A |
| Spring sleeve cpl., with vacuum connection (in connection with finder, see catalog: Inserting Tools D3320E) | Part no. | - | 364672A | 364672C | 364680D |



It is necessary to use a torque support (e.g. stand, handgrip) for maximum torque: over 4 Nm for straight handle design.
Suitable torque supports can be found in our catalog D3345E.



Please also find suitable tool inserts in our catalog D3320E.

DEPRAG

DEPRAG SCHULZ GMBH u. CO. KG

P.O. Box 1352 | D-92203 Amberg

Carl-Schulz-Platz 1 | D-92224 Amberg

Phone: +49 9621 371-0 | Fax: +49 9621 371-120

www.deprag.com | info@deprag.de

CERTIFIED AS PER DIN EN ISO 9001
