

MINIMAT Screwdrivers

The basic solution for almost all screwdriving tasks

pistol grip design - torque from 0.3 to 20 Nm / 2.7 to 177 in.lbs

- robust
- highest precision
- ergonomic
- long-life
- low noise level

The particular strength of the MINIMAT screwdriver in pistol grip design is that it can carry out screw assemblies with torque ranges from 0.3 Nm to 20 Nm. In these ranges you can not only assemble screws but also adjust them.

The ergonomic MINIMAT screwdriver is extremely durable due to its extraordinary processing quality and design for heavy industrial use.

The highly precise shut-off clutch allows torque precision of $\leq 3\%$ standard deviation, which is maintained for millions of assemblies. When used under the correct conditions DEPRAG pneumatic screwdrivers with shut-off clutch conform with a Cmk value of ≥ 1.67 with 15% tolerance in relation to 6 Sigma according to ISO 5393.

In other words a Cmk value of 1.67 means that there is a failure rate of 0.6 per million screw assemblies.

Handheld Screwdriver pneumatic



TECHNICAL DATA

MINIMAT Screwdrivers - pistol grip design

Screwdriver style			Motor Size 2			
Reversible, trigger-start Lower air-inlet	Type Part no.	347-227U 394569A	347-327U 394569B	347-427U 394569D	347-527U 394569C	
Reversible, trigger-start Upper air-inlet	Type Part no.	347-227OU 394570A	347-327OU 394570B	347-427OU 394570D	347-527OU 394570C	
Reversible, push-to-start Lower air-inlet	Type Part no.	347-229U 394573A	347-329U 394573B	347-429U 394573D	347-529U 394573C	
Reversible, push-to-start Upper air-inlet	Type Part no.	347-229OU 394574A	347-329OU 394574B	347-429OU 394574D	347-529OU 394574C	
Screws	up to	M3	M4	M4	M5	
Torque	min.	Nm / in.lbs	0.5 / 5	0.4 / 4	0.4 / 4	
Torque (soft pull-up)	max.	Nm / in.lbs	1.3 / 11	3 / 26	3.5 / 31	
Torque (hard pull-up)	max.	Nm / in.lbs	1.5 / 13	3.2 / 28	4 / 35	
Speed, idling	rpm	3000	1100	750	500	
Air consumption	m ³ /min / cfm	0.3 / 11	0.3 / 11	0.3 / 11	0.3 / 11	
Distance from spindle centre to side	mm / in.	14.5 / ⁹ / ₁₆	14.5 / ⁹ / ₁₆	14.5 / ⁹ / ₁₆	14.5 / ⁹ / ₁₆	
Length	mm / in.	208 / 8 ³ / ₁₆	208 / 8 ³ / ₁₆	208 / 8 ³ / ₁₆	208 / 8 ³ / ₁₆	
Weight	kg / lbs	0.75 / 1.6	0.75 / 1.6	0.75 / 1.6	0.75 / 1.6	
Noise level	dB(A)	69	69	69	69	
Screwdriver style			Motor Size 2.5			
Reversible, trigger-start Lower air-inlet	Type Part no.		346-7257U 412799A	346-3257U 412799B	346-4257U 412799C	
Reversible, push-to-start Lower air-inlet	Type Part no.		345-7259U 390854A	345-3259U 390854B	345-4259U 390854C	
Screws	up to		M5	M6	M6	
Torque	min.	Nm / in.lbs	1 / 9	1 / 9	1 / 9	
Torque (soft pull-up)	max.	Nm / in.lbs	5 / 44	10 / 88	12 / 106.2	
Torque (hard pull-up)	max.	Nm / in.lbs	6 / 53	10 / 88	12 / 106.2	
Speed, idling	rpm		1025	525	270	
Air consumption	m ³ /min / cfm		0.35 / 12	0.35 / 12	0.35 / 12	
Distance from spindle centre to side	mm / in.		20 / ²⁵ / ₃₂	20 / ²⁵ / ₃₂	20 / ²⁵ / ₃₂	
Length	mm / in.		240 / 9 ⁷ / ₁₆	240 / 9 ⁷ / ₁₆	240 / 9 ⁷ / ₁₆	
Weight	kg / lbs		1.2 / 2.6	1.2 / 2.6	1.2 / 2.6	
Noise level	dB(A)		72	72	72	
Screwdriver style			Motor Size 3			
Reversible, trigger-start Upper air-inlet, lower air-inlet or rear air-inlet	Type Part no.	346-237U 400373B	346-737U 400373C	346-337U 400373D	346-437U 400373E	
Reversible, push-to-start Upper air-inlet, lower air-inlet or rear air-inlet	Type Part no.	346-239U 411447B	346-739U 411447C	346-339U 411447D	346-439U 411447E	
Screws	up to	M5	M6	M6	M8	
Torque	min.	Nm / in.lbs	2 / 17.7	2 / 17.7	2 / 17.7	
Torque (soft pull-up)	max.	Nm / in.lbs	4.5 / 39.8	7 / 62	12 / 106.2	
Torque (hard pull-up)	max.	Nm / in.lbs	5.5 / 48.7	8 / 70.8	12 / 106.2	
Speed, idling	rpm	2300	1200	650	320	
Air consumption	m ³ /min / cfm	0.4 / 14	0.4 / 14	0.4 / 14	0.4 / 14	
Distance from spindle centre to side	mm / in.	21 / 0.8	21 / 0.8	21 / 0.8	21 / 0.8	
Length	mm / in.	280 / 10.9	280 / 10.9	280 / 10.9	280 / 10.9	
Weight	kg / lbs	1.6 / 3.5	1.7 / 3.75	1.7 / 3.75	1.7 / 3.75	
Noise level	dB(A)	72	72	72	72	

Performance data relate to an air pressure of 6.3 bar (90 PSI), Air hose dia. 6 mm/1/4", Internal hex. drive DIN ISO 1173 – F6.3 (1/4"), integrated quick change chuck

Included in delivery:

Hose coupling with nozzle and nipple · Torque adjustment tools · Assortment of clutch springs

The screwdrivers motor sizes 2, 2.5 and 3 can also be delivered with an automatic screw feed system. Please contact us for more information!

The screwdrivers motor size 2 are also available in explosion-proof design. Please contact us for more information!

Suitable tool inserts and connecting components with a drive as per DIN ISO 1173 E6.3 (1/4"), see also in our brochure D3320E – Inserting tools.

TECHNICAL DATA

MINIMAT Screwdrivers - pistol grip design

Screwdriver style			Motor Size 4		
Reversible, trigger-start	Type		344-347U	344-447U	344-247U
Upper air-inlet, lower air-inlet or rear air-inlet	Part no.		400320D	400320E	400320F
Reversible, push-to-start	Type		344-349U	344-449U	344-249U
Upper air-inlet, lower air-inlet or rear air-inlet	Part no.		411448D	411448E	411448F
Screws	up to		M5	M6	M8
Torque min.	Nm / in.lbs		3 / 26	3 / 26	2 / 17.7
Torque (soft pull-up) max.	Nm / in.lbs		6.5 / 57.5	8 / 70.8	17 / 150.5
Torque (hard pull-up) max.	Nm / in.lbs		8.5 / 75.2	10 / 88.5	17 / 150.5
Speed, idling	rpm		2300	1600	650
Air consumption	m ³ /min / cfm		1 / 35.3	1 / 35.3	1 / 35.3
Distance from spindle centre to side	mm / in.		21 / 0.8	21 / 0.8	21 / 0.8
Length	mm / in.		292 / 11.4	292 / 11.4	311 / 12.1
Weight	kg / lbs		1.7 / 3.7	1.7 / 3.7	1.95 / 4.3
Noise level	dB(A)		81	81	81

Performance data relate to an air pressure of 6.3 bar (90 PSI), Air hose dia. 10 mm/1/4", Internal hex. drive DIN ISO 1173 – F6.3 (1/4"), integrated quick change chuck

Included in delivery:

Hose coupling with nozzle and nipple · Torque adjustment tools · Assortment of clutch springs

► Suitable tool inserts and connecting components with a drive as per DIN ISO 1173 E6.3 (1/4"), see also in our brochure D3320E – Inserting tools.

Optional Equipment

		Motor Size 2	Motor Size 2.5	Motor Size 3	Motor Size 4
Spring-Sleeve cpl., without screw suction	Part no.	364672A	364680A	364672A	364672A
Spring-Sleeve cpl., with screw suction (in connection with finder, see leaflet: Inserting Tools D 3320 E)	Part no.	364672C	364680D	364672C	364672C
Exhaust hose (0.75 m / 2.5 ft.) with air hose (2 m / 6.6 ft.)	Part no.	–	330628A	413417A	413417A
Handle	Part no.	–	–	4109711	4109711



It is necessary to use a torque support (e.g. stand, handgrip) for maximum torque: over 10 Nm for pistol grip.
Suitable torque supports can be found in our brochure D3345E.

► The screwdriver is actuated by trigger. If needed, exhaust hoses can be connected to the screwdriver; this will direct exhaust air away from the assembly area. For size 3 pistol-grip drivers, we offer additional side-handles, which are an useful addition for higher torque values.

DEPRAG

DEPRAG SCHULZ GMBH u. CO.

P.O. Box 1352, D-92203 Amberg, Germany
Carl-Schulz-Platz 1, D-92224 Amberg
Phone (+49) 9621 371-0, Fax (+49) 9621 371-120
www.deprag.com
info@deprag.de

CERTIFIED AS PER DIN EN ISO 9001
